

SAVITLJIVI KABL · FLEXIBLE CORD

H03VVH2-F

Pljosnati laki savitljivi kabl sa PVC izolacijom i plaštom (H03VVH2-F), 300/300 V, za lake primene.

Flat light-duty PVC-insulated and sheathed flexible cord (H03VVH2-F), 300/300 V.



PRIMENA / APPLICATION

Za kućne prostorije i kancelarije, za lake primene i aparate (audio oprema, stone i stojeće lampe, kancelarijska oprema). Nije za termičke uređaje, spoljašnju upotrebu ni komercijalne objekte.

For domestic premises and offices, for light duty and appliances (music equipment, table and standard lamps, office equipment). Not for heating devices, outdoor use or commercial facilities.

KONSTRUKCIJA / CONSTRUCTION

Provodnik / Conductor: Bakarno uže, klasa 5 / Cu rope, cl.5

Izolacija / Insulation: PVC smeša / PVC compound

Plašt / Sheath: PVC, beo ili crn / PVC, white or black

Identifikacija / Core ID: HD 308 S2

IDENTIFIKACIJA ŽILA / CORE ID

2 žile: braon, plava (HD 308 S2). Plašt: beo ili crn; druge boje na upit.

2-core: brown, blue (HD 308 S2). Sheath: white or black; other colours on request.

TEHNIČKE KARAKTERISTIKE / SPECS

Napon U ₀ /U / Voltage	300 / 300 V
-----------------------------------	-------------

Ispitni napon / Test voltage	2 kV (AC)
------------------------------	-----------

CPR klasa / CPR class	Eca
-----------------------	-----

Maks. temp. provodnika / Max. cond.	70 °C
-------------------------------------	-------

Temp. kratkog spoja / Short-circuit	150 °C
-------------------------------------	--------

Temp. opseg / Temp. range	-15 ... +70 °C
---------------------------	----------------

STANDARDI / STANDARDS

EN 50525-2-11 · IEC 60332-1-2 · HAR (BBJ)

DIMENZIJE I ELEKTRIČNI PODACI / DIMENSION & ELECTRICAL DATA

Žile x presek CORES x SECT.	Ø provodnika CONDUCTOR Ø	Deblj. izol. INSUL. THK.	Deblj. plašta SHEATH THK.	Dimenzije OUTER DIM. (h x w)	Masa WEIGHT	Radius savij. BEND RADIUS	Otpor 20°C RESISTANCE	Maks. sila PULL FORCE
n x mm ²	mm	mm	mm	mm	kg/km	mm	Ω/km	N
2x0,5	0,9	0,5	0,6	3,0 x 4,8	25	19	39,0	50
2x0,75	1,1	0,5	0,6	3,2 x 5,2	32	21	26,0	75

NAPOMENE / NOTES

- Ispod +5 °C kabl ne sme biti mehanički naprezan; minimalna temperatura skladištenja -15 °C. / Below +5 °C the cable must not be mechanically stressed; minimum storage temperature -15 °C.
- Maksimalna sila zatezanja raspoređuje se na sve provodnike kabla. / The maximum pulling force is distributed over all cable conductors.
- Sve vrednosti su orijentacione i podložne izmenama bez najave. / All values are indicative and subject to change without notice.